Derope[™] rescue kit and Evak[™]

DEROPE™ RESCUE KIT

A complete kit for evacuation at heights.

Contents of the rescue kit

- Derope UP A for upwards and downwards evacuation
- 10.5 mm braided rope with a length of 85, 120 or 150 m and 3 M48 tri-lock karabiners
- 1 patented Tractel rope reel
- 1 braided rope protector
- 1 lanyard spreader device with connector to keep the rope from the structure
- 1 Stopfor[™] K to disconnect the fall arrest lanyard from the user
- 2 strap rings to connect the Derope[™] and the pulley onto the structure
- 1 pulley to position the braided rope in the optimal position during descent
- 4 M23 tri-lock connectors
- 1 waterproof box with shock absorbing foam

Advantages

- Complete with Derope[™] UP A for fast and safe evacuation
- Complete equipment ready to use
- Strong and waterproof box
- Overpressure valve to protect against condensation
- Humidity indicator
- н. Humidity absorption bags
- Storage box seal lets you know if the kit has been opened
- If the seal is unbroken, the kit doesn't require inspection for 5 years н.

Specification

- Dimensions (H x L x D): 225 mm x 200 mm x 165 mm
- Max load recovery: 150 kg (400 m) or 225 kg (150 m) .
- EN 341 class A + EN 1496 class A standards
- Descent speed: 0.5 m/s 2 m/s

model	code
Derope™ rescue kit 85 m	222949
Derope™ rescue kit 120 m	222959
Derope™ rescue kit 150 m	222969





New rope reel removes the risk of tangling when the rope is thrown





EVAK™

The Evak™ 500 is a manual rope winch offering unlimited travel, with a 500 kg capacity. Designed especially for rescue operations. Static rope with a diameter between 10.5 and 12.5 mm.



code
023498

¹⁾ without rope

model¹⁾

Evak™ 500

EVAK[™] ACCESSORIES

model	code
Rope 12.5 mm, 20 m	046059
Rope 12.5 mm, 40 m	046069
Rope 12.5 mm, 60 m	046079
Rope 12.5 mm, 80 m	046089
Rope 12.5 mm, 100 m	046099
Rope 12.5 mm, 200 m	046109

www.tractel.com